Mr./Mrs/Ms:				Mod	del:					Reg.No:	
Invoice/Job no:					_ Odd	meter r	eading:				V.I.N:
Service type:	Α	В	Α	В	Α	В	Α	В	Α	В	7
Months/,000 miles:	12	24	36	48	60	72	84	96	108	120	
Adirection by instal (Danisas - Laboury and included in appealuled time groups themse wouldn't											



Adjust/Lubricate/Replace - Labour cost included in scheduled time except items marked

33. 36k 72k Renew full flow filter - *Diesel*

Check - After the checking procedure, cleaning, adjusting, repairing or replacing is subject to extra labour and material cost.

А В	VEHICLE INTERIOR	А	В	MAIN SERVICE (UNDER VEHICLE)
1.	Check condition and security of seats and seat belts	34.		Renew engine oil filter - <i>V8</i>
2.	Check operation of all lamps, horns and warning indicators	35.		Renew manual gearbox oil
3.	Check operation of front/rear wipers and washers and condition of wiper blades	36.	٦	Check and top up manual gearbox oil
4.	Check operation of handbrake	37.		Renew automatic transmission filter - First 24,000 miles only
5.	Replace alarm handset batteries	38.		Renew automatic transmission oil
	VEHICLE EXTERIOR	39.		Renew transfer box oil
	Annual corrosion/cosmetic inspection - Only on vehicles sold after 21/11/98	40.		Check and top up transfer box oil
6.	Remove road wheels	41.	96k	Renew front and rear axle oil
8.	Check tyre pressures, condition and tread depth.	42.		Check and top up front and rear axle oil
0.	LHF RHF RHR LHR Spare	43.		Lubricate propeller shaft universal/sliding joints
		44.		Check for free play in anti-roll bar links and condition of rubber boots
9.	Inspect brake pads for wear, calipers for leaks and discs for condition	45.		Check condition of gaiters to ACE actuators
10. 📖 🚐	Inspect road whel speed sensor harness for damage	46.	72k	Replace ACE filter in valve block and replace lost fluid
11.	Replace Brake Fluid (Every 2 years)	47.		Check visually, brake servo hose, brake, fuel, clutch pipes, unions, ACE pipes and
12	Renew fuel filter element (Diesel)			electrical harnesses for chafing, leaks and corrosion.
13.	Drain fuel sedimenter (<i>Diesel only</i>)	48.		Check for fluid leaks from power steering and suspension systems hydraulic pipes and
14	Refit road wheels to original hub position (Use anti-sieze compound on spigot bore)			unions for chafing and corrosion
15	Visually check intercooler/radiator for external obstructions and fan blades for damage	49.	-	Check for fluid leaks from Engine, Gearbox, Transfer box and Axles
16	Check ambient air sensor for damage	50.	401	Check exhaust system for leaks, security and damage
17.	Check operation and Lubricate door locks, hinges, door checks, bonnet catch & fuel flap	51.	48k	
18. <u>60k</u> 120k	Check condition of air suspension intake filter - See recommendations	52.	-	Check steering rod ball joint fixings and condition of ball joints and dust covers
	UNDER BONNET	53.	-	Check shock absorbers/height sensors and harness assembly for leakage and damage
19. 36k 72k	Renew anti-freeze	54		Check/tighten front and rear axle suspension link fixings, check condition of mounting rubbers
20.	Check cooling, intercooler and heating systems for leaks, hoses and oil pipes for	55.		Check security of towing bracket
	security and condition . Top up as required	56.	48k	
21. <u>72k</u>	Renew spark plugs	57.		If fault lamp(s) are illuminated, interrogate that system using TestBook and report
22	Renew air cleaner element and clean drain hole (V8)	<i>37</i>		findings
23. 36k 72k	Renew air cleaner element and clean dump valve (Diesel)	58.		Carry out road or roller test (see WARNING over page)
24	Check condition of ancillary driving belt	59.		Endorse service record
25. 48k	, , ,	60.		Report any unusual features of vehicle condition and additional work required
26. <u>96k</u>	, , ,	The maint	enance i	tems listed, are those recommended for vehicles operating under normal driving, road and climatic conditions. Mor
27.	Check/top up brake, PAS, clutch and ACE fluid levels and screen washer reservoirs	frequent a	ttention i	may be necessary if the vehicle is subject to stop/start operation, extremes of temperature, dusty conditions, off roar
	Check/adjust steering box	driving or f	requent t	towing of trailers.
29.	Check battery condition	Service ch	eck com	pleted and service portfolio book endorsed
30. 48k				
31	Renew engine oil	Name:		Signature: Date:
32.	Renew centrifuge rotor - Diesel			•

06/01 LRL 0338ENG(2)

WARNING:

Two wheel roller tests must not be carried out. Four wheel roller tests must be restricted to 5Km/hour (3miles/hour).

IMPORTANT

OIL CHANGE DIESEL ENGINES

If the vehicle is operated on fuel with a high sulphur content (over 1%) the oil change intervals must not exceed 10,000Km (6000 miles)

VEHICLES FITTED WITH SUPPLEMENTARY RESTRAINT SYSTEMS

The seatbelt pre-tensioners (where fitted) and air bags must be replaced every FIFTEEN YEARS

Side air bags must be replaced every FIFTEEN YEARS

IT IS RECOMMENDED THAT:

At 120,000 Km (72,000 miles) or every six years, whichever is the sooner, all hydraulic brake fluid seal and hoses should be renewed.

All working surfaces of the caliper cylinders should be examined and renewed where necessary.

Vehicles used extensively in arduous/off road conditions - check the road wheel speed sensors, brake pads and calipers for abrasive wear at 1500 km (1000 miles) intervals

Air suspension vehicles used extensively in arduous/off road conditions will require the compressor inlet filter to be replaced at more regular intervals .

The Power Steering/ACE fluid reservoir should be replaced at 250,000Km (156,000 miles)

When the vehicle is used in dusty or field conditions or deep wading, frequent attention to the air cleaner may be required.

When the vehicle is used in areas where fuel quality is poor, more frequent draining of the fuel filter/sedimentor may be required.

For full details regarding the operations contained in this maintenance check sheet, please refer to the workshop manual.

GLOSSARY

MAIN SERVICE = The main service is applicable to all vehicles. It is carried out at 12 month or 12,000 miles intervals, whichever occurs first.

Main Service "A"is applicable at 12 months/12,000 miles, 36 months/36,000 miles, 60 months/60,000 miles 84 months/84,000 miles and so on.

Main Service "B"is applicable at 24 months/24,000 miles, 48 months/48,000 miles, 72 months/72,000 miles, 96 months/96,000 miles and so on. Some items do not need to be carried out at every main service and these items are identified by an indicator in the tick box e.g. 60k (This indicates that this item is only applicable every 60 months/ 60,000 miles)